

Accumulator Precharging Equipment

For Safe-Easy Precharging of Hydraulic Accumulators, We offer a compressive range of equipment including Charging Sets, International Connections, Accessories & Nitrogen Charging Regulators with pressure gauges ranging up to 400 bar. High Pressure Boosters up to 345 bar are available in Hydraulic & Electric Models



for use with Diaphragm & Bladder Accumulators



for use with Bladder Accumulators

Ordering Features :-

105 - 00 - ** - ***

TYPE

105 – Bladder Type ¼" BSP
CKD – Diaphragm Type M28x1.5
UCK – Diaphragm & Bladder (Universal)

CHARGING HOSE

03 – 2.5 mtr ** - Special Specify

PRESSURE GAUGE

01 – 0 to 10 bar. **02** – 0 to 21 bar. **03** – 0 to 60/70 bar.
04 – 0 to 140/ 160 bar **05** – 0 to 250/280 bar **06** – 0 to 400 bar.
**-Other ranges on request

ADAPTORS

TYPE 105

A– ¼" BSP(M) x 5/8" UNF (F)
B – ¼" BSP(M) x 7.7 x 32 TPI

TYPE CKD

C- M28 x 1.5(M) x ¼" BSP(F)
D- M28 x 1.5(M) x 7/8" UNF(F)
E- M28 x 1.5(M) x 5/8"UNF(F)
F- 7.7 x 32 TPI

TYPE UCK

Adaptors **C,D,E & F**
Included

(Note : - Accumulator Model & Gas Valve details to be indicated at the time of ordering)